



Customer Product Specification



Product Description	MPS 110mm Ribbed Cap, Black , with IHS Wad (Selig safe gard 960 plus)
Product Code	A1-110N-04 IHS

Product Photograph	Product Details				
	Nominal Weight	17.0g	Process	Injection Moulding	
	Neck Size	110mm			
	Wad Material				
	Induction Heat Seal IHS (Selig Safe-gard 960 plus)				
	Materials				
	Description	%	Ref Code	Supplier	
	Polypropylene	99	RM1001	Hardie Polymers	
	Black Masterbatch	1	MB2009	Gabriel Chemie	
	Packaging Information				
	Packaging Description	Product is tumble packed into a lined cardboard box. The boxes are taped, sealed and palletised, The pallet is stretch wrapped for stability			
	Box Qty	300	Pallet size	Std 1.2m x 1.0m	
	Pallet Height	2.6m	Pallet Quantity	7000	
	Boxes on pallet	25			
Half height Pallet Specification Information					
Signed	 Iain Mcleod		Date	15 th March 2022	

Customer Product Specification

Product Description MPS 110mm Ribbed Cap, Black, with IHS Wad (Selig safe gard 960 plus)
Product Code 12-110N-04 IHS



Freshness and Protection for Today's Packaging

Safe-Gard plus™ Technical Data Sheet

1.0mm Safe-Gard plus-960

Revision: SGPLUS960-10072016

Product	1.0mm Safe-Gard plus™ 960		
Scope	Two piece pulp backed heat induction foil innerseal that will provide a weld seal to PET and PVC containers.		
Composition	Material	Standard	Metric
	Pulp	0.036"	0.90mm
	Wax	-	16gsm
	Foil	0.001"	0.025mm
	Heat Seal	0.0006"	0.015mm
	Adhesive or resin bonding layers not shown.		
FDA Status: Upon request	Recommended Storage and Handling: Refer to website		
Drug Master File (DMF):	EU / EP Reg.: 1935/2004/EC, 10/2011/EC, 2023/2006/EC		
GTR Oxygen: Essentially Zero	MVTR: Essentially Zero		
Print Location (if any): On foil layer			

Selig materials are compliant with limitation of heavy metals in packaging per CONEG & EU 94/62/EC, article 11.

MSDS's are not required as Selig is not a chemical manufacturer or distributor and our products are 'articles' intended for food packaging per 29 CFR 1910.1200 (HazCom).

The information contained within this product data bulletin is to be used as a general guide in determining which structures are offered for sealing to specific container materials. All of the information which we provide is reliable to the best of our knowledge, but the accuracy thereof is not guaranteed. We suggest that consumers determine suitability for their own application.

www.seligsealing.com

Corporate Headquarters
Selig Sealing Products, Inc.
342 E Wabash St
Forrest, IL 61741, USA
Phone: +1 (815) 785-2100
Fax: +1 (815) 657-7584

North American Sales
Selig Sealing Products, Inc.
184 Shuman Blvd., Suite 310
Naperville, IL 60563, USA
Phone: +1 (630) 922-3158
Fax: +1 (630) 922-8469

European Sales and Manufacturing
Selig UK, LTD 635-637 Ajax Avenue
Slough Trading Estate
Slough Berkshire SL14BH UK
Phone: +44 (0) 1753 773 000
Fax: +44 (0) 1753 773 111

Canadian Manufacturing
Selig Canada, ULC
145 Edward Street
Aurora, Ontario Canada, L4G 1W3
Phone: +1 (905) 727-0114
Fax: +1 (905) 727-8544

Swiss Manufacturing
Selig Switzerland LTD
Bahnhofstrasse 11
CH-8172 Niederglatt
Phone: +41 (0) 44 851 50 50
Fax: +41 (0) 44 851 50 51

All Selig manufacturing facilities are ISO 9001 certified. For details, visit www.seligsealing.com/certifications